





SCISSOR LIFT CONFIGURATION

The bench combined with a special scissor lift is mobile and inclinable on both ends.

Its dimensions have been optimized to allow the maximum accessibility, both inside and outside the frame during the entire repair process in order to work in an efficient ergonomics approach.

Its technical specifications enable the end-user to carry out realignment operations when repairing passenger's cars, light commercial, off-road vehicles and pick-up while maintaining a comfortable working posture.

The frame is manufactured using a high tensile steel which is milled to ensure a precise positioning of the checking points and powder painted.


Approach ramps and side runners thanks to their specific design allow the loading on board of the vehicle without dismantling the basic equipment.













Pit mounted Version 3

MANTA



TECHNICAL FEATURES

MOBILE BENCHES WITH MANTA FRAME

Bench Lenght	4,5 m (15')	5,2 m (17')	6,0 m (20')
Frame weight	640 Kg	730 Kg	860 Kg

LIFTS WITH MANTA FRAME	SCISSOR LIFT WITH 4,5 TON LOAD CAPACITY		SCISSOR LIFT WITH 6,0 TON LOAD CAPACITY	
Bench Length	4,5 m (15')	5,2 m (17')	5,2 m (17')	6,0 m (20')
Load Capacity	4,5 ton (9,920 lb)		6,0 ton (13,300 lb)	
Min. lifting height	320 mm (1')		320 mm (1')	
Max. lifting height from working area	1800 mm (5' 90")		1800 mm (5' 90")	
Weight of lift with frame	1,3 ton	1,4 ton	1,4 ton	1,5 ton
Nominal Power	2 Kw		2 Kw	
Nominal Voltage	380 V		380 V	
Nominal Current	4,3 A		4,3 A	
Nominal Frequency	50 Hz		50 Hz	
Max pressure when lifting	280 Bar		280 Bar	
Max pressure when lowering	130 Bar		130 Bar	

PULL POSTS

Pulling power

10 ton CARBENCH

CAR BENCH TRAINING ACADEMY

REPAIR METHODS

CAR BENCH EQUIPMENT TRAINING

MANTA

CUSTOMIZED **OEM TRAININGS**



Car Bench International S.p.A.

Via Dorsale, 22 - 54100 Massa (MS) - ITALY info@carbench.it - ph. +39 0585 251261 www.carbenchinternational.com





